



HTDM Tubo stratificato con 2 bicchieri

Codice	DN	D max	L mm.	S1-min mm.	t-min mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
TDM090500	90	104,5	500	2,2	58,8	0,459	15	90	7,10
TDM091000	90	104,5	1000	2,2	58,8	0,794	4	96	10,60
TDM091500	90	104,5	1500	2,2	58,8	1,128	4	96	14,90
TDM092000	90	104,5	2000	2,2	58,8	1,423	4	96	18,80
TDM093000	90	104,5	3000	2,2	58,8	2,098	4	96	28,10
TDM110500	110	127,1	500	2,7	64,6	0,738	10	60	8,50
TDM111000	110	127,1	1000	2,7	64,6	1,270	4	60	12,10
TDM111500	110	127,1	1500	2,7	64,6	1,806	4	60	17,50
TDM112000	110	127,1	2000	2,7	64,6	2,325	4	60	22,40
TDM113000	110	127,1	3000	2,7	64,6	3,357	4	60	32,40
TDM120500	125	144,0	500	3,1	69,0	0,954	6	54	13,70
TDM121000	125	144,0	1000	3,1	69,0	1,617	4	48	19,80
TDM121500	125	144,0	1500	3,1	69,0	2,287	4	48	27,00
TDM122000	125	144,0	2000	3,1	69,0	2,929	4	48	36,80
TDM123000	125	144,0	3000	3,1	69,0	4,328	4	48	50,00

HTB Curva

Codice	DN	α	Z1 mm.	Z2 mm.	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BBO032015	32	15°	2,0	3,0	62,0	0,020	50	2400	1,00
BBO032030	32	30°	3,0	7,0	63,0	0,020	50	2400	1,00
BBO032045	32	45°	4,0	16,0	51,0	0,022	50	3600	1,00
BBO032067	32	67,5°	7,0	11,0	64,5	0,023	50	2400	1,05
BBO032087	32	87,5°	14,0	25,0	62,0	0,024	50	3600	1,00
BBO040015	40	15°	2,0	9,0	51,0	0,030	20	960	0,92
BBO040030	40	30°	3,0	12,0	53,0	0,031	20	960	0,92
BBO040045	40	45°	7,0	15,0	57,0	0,032	20	960	0,88
BBO040067	40	67,5°	16,0	20,0	78,5	0,034	20	960	0,97
BBO040087	40	87,5°	16,0	30,0	66,0	0,036	20	960	0,88
BBO050015	50	15°	5,0	9,0	60,0	0,045	20	960	1,15
BBO050030	50	30°	14,0	10,0	69,0	0,045	20	960	1,15
BBO050045	50	45°	14,0	16,0	64,0	0,041	20	960	1,11
BBO050067	50	67,5°	20,0	28,0	72,0	0,052	20	960	1,31
BBO050087	50	87,5°	23,0	35,0	52,0	0,047	20	960	1,15