



HTB Curva




Codice	DN	α	Z1 mm.	Z2 mm.	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BB0070015	75	15°	7,0	11,0	73,0	0,075	20	480	2,17
BB0070030	75	30°	12,0	15,0	83,0	0,079	20	480	2,22
BB0070045	75	45°	19,0	30,0	77,0	0,073	20	400	2,11
BB0070067	75	67,5°	28,0	31,0	93,0	0,088	20	480	2,28
BB0070087	75	87,5°	40,0	43,0	105,0	0,086	20	400	2,11
BB0090015	90	15°	6,0	13,0	78,0	0,084	20	400	3,10
BB0090030	90	30°	13,0	18,0	83,0	0,092	20	400	3,10
BB0090045	90	45°	20,0	26,0	87,0	0,102	20	400	3,00
BB0090067	90	67,5°	32,0	37,0	90,0	0,112	20	360	3,20
BB0090087	90	87,5°	46,0	53,0	96,0	0,118	20	360	3,00
BB0110015	110	15°	7,0	20,0	68,0	0,154	20	240	3,60
BB0110030	110	30°	27,0	22,0	86,0	0,166	20	240	3,60
BB0110045	110	45°	10,0	34,0	84,0	0,181	20	240	3,55
BB0110067	110	67,5°	40,0	44,0	116,0	0,194	20	160	3,68
BB0110087	110	87,5°	58,0	72,0	115,0	0,215	20	160	3,60
BB0120015	125	15°	10,0	15,0	92,0	0,221	20	160	9,00
BB0120030	125	30°	19,0	23,0	100,0	0,244	20	160	9,00
BB0120045	125	45°	26,0	44,0	106,0	0,276	20	160	7,80
BB0120087	125	87,5°	65,0	83,0	147,0	0,318	10	120	7,80
BB0160015	160	15°	13,0	22,0	113,0	0,420	10	80	20,00
BB0160030	160	30°	24,0	32,0	123,0	0,456	10	80	20,00
BB0160045	160	45°	32,0	55,0	140,0	0,493	10	80	18,00
BB0160087	160	87,5°	87,0	98,0	180,0	0,594	10	60	19,00

HTEA Braga



Codice	DN D/D1	α	Z1 mm.	Z2 mm.	Z3 mm.	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BEA323245	32/32	45°	5,0	45,0	45,0	123,0	0,042	30	1440	2,35
BEA40345	40/32	45°	10,0	45,0	49,0	103,0	0,043	40	960	3,05
BEA40445	40/40	45°	8,0	54,0	54,0	116,0	0,070	20	960	1,72
BEA50445	50/40	45°	5,0	56,0	54,0	121,5	0,073	20	480	2,05
BEA50545	50/50	45°	10,0	65,0	65,0	125,0	0,088	20	480	2,18
BEA70445	75/40	45°	7,0	74,0	67,0	125,0	0,119	20	400	3,85
BEA70545	75/50	45°	1,0	79,0	74,0	139,0	0,102	20	240	3,85
BEA70745	75/75	45°	18,0	91,0	91,0	174,0	0,155	20	240	4,50
BEA90445	90/40	45°	10,0	92,0	75,0	134,0	0,180	20	360	4,40
BEA90545	90/50	45°	10,0	90,0	78,0	174,0	0,180	20	360	4,50

HTEA Braga



Codice	DN D/D1	α	Z1 mm.	Z2 mm.	Z3 mm.	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BEA090745	90/75	45°	9,0	103,0	105,0	207,0	0,182	20	240	6,80
BEA090945	90/90	45°	20,0	110,0	126,0	190,0	0,218	20	160	5,90
BEA110445	110/40	45°	27,0	100,0	90,0	146,0	0,218	20	160	4,35
BEA110545	110/50	45°	24,0	110,0	102,0	137,0	0,214	20	240	4,45
BEA110745	110/75	45°	6,0	127,0	127,0	186,0	0,261	20	160	6,55
BEA110945	110/90	45°	30,0	110,0	120,0	220,0	0,300	10	80	11,40
BEA111145	110/110	45°	20,0	141,0	141,0	221,0	0,382	10	80	5,80
BEA121145	125/110	45°	14,0	160,0	155,0	243,0	0,462	5	60	21,00
BEA121245	125/125	45°	30,0	155,0	155,0	258,0	0,618	5	40	27,00
BEA161145	160/110	45°	9,0	173,0	162,0	273,0	0,770	5	40	50,00
BEA161245	160/125	45°	17,0	193,0	180,0	283,0	0,851	5	40	59,00
BEA161645	160/160	45°	33,0	202,0	202,0	326,0	1,082	5	30	70,00
BEA323267	32/32	67,5°	16,0	24,0	33,0	93,0	0,044	30	1440	2,50
BEA040467	40/40	67,5°	16,0	33,0	33,0	110,0	0,060	20	960	2,30
BEA050467	50/40	67,5°	14,0	39,0	35,0	111,5	0,062	20	480	3,10
BEA050567	50/50	67,5°	20,0	41,0	41,0	121,5	0,078	20	480	3,28
BEA110567	110/50	67,5°	8,0	73,0	54,0	135,0	0,222	20	240	5,00
BEA111167	110/110	67,5°	40,0	88,0	77,0	184,0	0,350	10	120	6,90
BEA323287	32/32	87,5°	15,0	22,0	22,0	92,0	0,039	30	1440	2,40
BEA040387	40/32	87,5°	23,0	23,0	25,0	89,0	0,040	40	960	3,05
BEA040487	40/40	87,5°	20,0	28,0	28,0	99,0	0,059	20	960	1,72
BEA050487	50/40	87,5°	23,0	30,0	25,0	108,5	0,062	20	480	3,00
BEA050587	50/50	87,5°	27,0	32,0	32,0	112,0	0,084	20	480	2,25
BEA070587	75/50	87,5°	27,0	43,0	31,0	113,0	0,100	20	480	3,85
BEA070787	75/75	87,5°	40,0	43,0	43,0	148,0	0,118	20	240	4,50
BEA090587	90/50	87,5°	26,0	50,0	53,0	106,0	0,123	20	240	4,85
BEA090987	90/90	87,5°	56,0	70,0	103,0	154,0	0,186	20	160	5,90
BEA110487	110/40	87,5°	20,0	60,0	30,0	139,0	0,180	20	160	4,35
BEA110587	110/50	87,5°	26,0	67,0	42,0	125,0	0,192	20	240	4,65
BEA110787	110/75	87,5°	40,0	60,0	66,0	186,0	0,272	20	160	6,55
+ BEA110987	110/90	87,5°	57,0	47,0	83,0	173,0	0,413	10	120	11,40
BEA111187	110/110	87,5°	47,0	68,0	68,0	181,0	0,302	10	120	5,80
BEA121187	125/110	87,5°	58,0	76,0	73,0	220,0	0,438	5	60	22,00
BEA121287	125/125	87,5°	60,0	81,0	80,0	221,0	0,472	5	40	29,00
BEA161187	160/110	87,5°	58,0	86,0	64,0	237,0	0,642	1	40	52,00
BEA161687	160/160	87,5°	78,0	101,0	101,0	268,0	0,791	5	40	72,00