




HTS Raccordo tecnico diritto senza morsetto


Codice	DN D/D1	α	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BS0032000	32/46	90°	51,0	0,017	20	2400	1,85
BS0040100	40/46	90°	57,0	0,024	40	2880	0,64
BS0040400	40/50	90°	72,0	0,026	40	2880	0,64
BS0050500	50/60	90°	72,5	0,034	20	1440	1,43

HTSW Curva tecnica senza morsetto


Codice	DN D/D1	α	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BSW032000	32/46	90°	68,0	0,020	20	2380	1,80
BSW040100	40/46	90°	79,0	0,029	40	1600	0,72
BSW040300	40/40	90°	89,0	0,032	20	1920	1,35
BSW040400	40/50	90°	88,5	0,029	40	1600	0,72
BSW050400	50/50	90°	93,5	0,041	20	1440	1,30
BSW050500	50/60	90°	81,0	0,045	20	1200	1,70

HTSWPR Curva tecnica prolungata senza morsetto

Codice	DN D/D1	α	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BSWPR0401	40/46	90°	155,0	0,042	40	1560	0,98
BSWPR0404	40/50	90°	158,0	0,051	40	1560	0,98

HTDSW Curva tecnica doppia senza morsetto

Codice	DN D/D1/D2	α	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BDSW04540	50/50/50	90°	90,0	0,056	20	640	3,70

HTBR Curva ridotta

Codice	DN D/D1	α	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
BBR050487	40/46	90°	83,0	0,041	20	1200	1,70