



USB Curva



Codice		DN	α	Z1 mm.	Z2 mm.	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
US070015	7070030170	75	15°	7,0	14,0	63,5	0,138	20	600	3,09
US070030	7070030370	75	30°	12,0	18,0	68,5	0,148	20	600	3,09
US070045	7070030470	75	45°	18,0	24,0	74,5	0,159	20	600	2,98
US070067	7070030670	75	67,5°	29,0	35,0	85,5	0,119	20	480	4,20
US070087	7070030870	75	87,5°	43,0	49,0	99,5	0,197	20	480	4,09
US090015	7070090170	90	15°	8,0	16,0	68,0	0,178	20	480	4,28
US090030	7070090370	90	30°	14,0	20,5	74,0	0,192	20	320	4,28
US090045	7070090470	90	45°	21,0	27,5	81,0	0,206	20	320	3,98
US090067	7070090670	90	67,5°	34,0	40,0	94,0	0,230	20	320	4,74
US090087	7070090870	90	87,5°	50,0	56,0	110,0	0,254	20	320	4,32
US110015	7070040170	110	15°	6,0	19,0	78,0	0,252	20	240	4,68
US110030	7070040370	110	30°	16,0	25,5	85,0	0,271	20	240	4,68
US110045	7070040470	110	45°	25,0	33,5	94,0	0,300	20	240	4,16
US110067	7070040670	110	67,5°	44,0	48,0	110,0	0,331	20	240	5,09
US110087	7070040870	110	87,5°	60,0	66,0	129,0	0,367	20	240	4,56
US125015	7070050170	125	15°	12,0	21,9	87,0	0,335	10	160	9,35
US125030	7070050370	125	30°	29,0	30,0	104,0	0,408	10	160	9,35
US125045	7070050470	125	45°	29,0	38,0	104,0	0,370	10	160	9,12
US125087	7070050870	125	87,5°	67,0	73,0	142,0	0,457	10	160	13,03
US160015	7070060170	160	15°	8,0	22,0	99,0	0,665	5	80	14,60
US160030	7070060370	160	30°	27,0	29,0	105,0	0,652	5	80	14,60
US160045	7070060470	160	45°	36,0	44,0	116,0	0,760	5	60	14,60
US160087	7070060870	160	87,5°	79,5	81,0	162,0	0,985	5	60	22,54
US200045	7070080470	200	45°	49,0	63,0	148,0	1,521	3	36	68,33

USEA Braga



Codice		DN D/D1	α	Z1 mm.	Z2 mm.	Z3 mm.	L mm.	Peso Kg./pz.	Conf. Pezzi	Conf. Bancale	€/Pz.
US030345	7070600470	32/32	45°	9,0	42,0	42,0	95,0	0,091	20	1200	3,14
US040445	7070611470	40/40	45°	11,0	52,0	52,0	111,0	0,130	20	800	3,22
US050445	7070621470	50/40	45°	13,0	64,0	57,0	129,0	0,164	20	600	4,03
US050545	7070622470	50/50	45°	13,0	64,0	64,0	129,0	0,182	20	600	3,74
US070545	7070632470	75/50	45°	18,0	95,0	100,0	170,0	0,302	20	320	5,26
US070745	7070633470	75/75	45°	18,0	95,0	95,0	170,0	0,335	20	320	5,51
US090445	7070691470	90/40	45°	32,5	112,5	92,0	205,0	0,280	10	180	7,74
US090545	7070692470	90/50	45°	32,5	112,5	89,0	205,0	0,383	10	180	8,42
US090945	7070699470	90/90	45°	33,0	113,0	112,5	206,0	0,464	10	120	8,60
US110445	7070641470	110/40	45°	17,0	112,0	96,5	148,5	0,440	10	160	9,37